






30F

AGG. 10/20

3~ 50 Hz. 400V	
FPT INDUSTRIAL	
EU STAGE 0	
69 dB(A) @ 7 mt	
100 lt	

PRIME POWER		STAND-BY POWER	
kVA	kW	kVA	kW
30	24	33	26,4

ENVIRONMENTAL CONDITIONS	
Temperature	40° C
Height	1000 mslm
Humidity	60%

OPEN VERSION B50



SOUNDPROOF VERSION C30



The image is only for demonstration purposes

WEIGHT	DIMENSIONS		
	L [mm]	W [mm]	H [mm]
kg			
690	1650	850	1600

WEIGHT	DIMENSIONS		
	L [mm]	W [mm]	H [mm]
kg			
865	1800	850	1275

TECHNICAL DETAILS

ELECTRICAL DATA	Electrical system type	3F+N	~
	Power factor	0,8	φ
	Voltage	400	V
	Frequency	50	Hz
	PRP Ampere rating	43,3	A
ENGINE	Engine	FPT S8000 AM1	
	Engine emissions standard	EU STAGE 0	
	RPM governor	Electronic	
	Performance class	G3	
	Rpm	1500	rpm
	Nr. of cylinders	3	
	Bore x stroke	104 x 115	mm
	Displacement	2900	cc
	Induction system	Natural	
	Cooling system	Water	
	Engine net prime power	37,7 (28,1)	Hp (kW)
Exhaust gas aftertreatment	/		
CONSUMPTION	Fuel type	Diesel	
	Consumption @ 50-75-100% load	3,8 – 5,4 – 7,2	lt/h
	Standard tank capacity	100	lt
	Autonomy	18,5	h
ALTERNATOR	Alternator	MECC ALTE	
	Type	Self excited, brushless	
	Number of poles	4	
	Insulation class	H	
	Temperature rise class	H	
	Voltage regulation	AVR	
Voltage precision	± 1	%	
GENERAL	Sound level (soundproof version)	69	dB(A) 7mt
	Exhaust pipe diameter	60	mm
	Electrical system voltage	12	V

ELECTRIC PANEL

MANUAL

AUTOMATIC MAINS FAILURE



Electronic control unit with multimeter	LOVATO ELECTRIC RGK420SA	COMAP IntelliLite 9
Electrical panel enclosure protection degree	IP44	
ON-OFF electric panel switch	Key type. In-built the control unit	Without key
Emergency pushbutton	STANDARD	
Battery charge maintainer	/	12V 3A
Power supply	ECC IP67 sockets: n.1 3P 16A + n.1 5P 63A	Full power terminal
Circuit breaker	Magnetothermal type 1P+N 16A and 4P 40A	Magnetothermal type 4P 40A
Main protection alarms	Min-max V and Hz. LOP. HWT. Battery charger alternator failure. Low fuel level	

STANDARD ELECTRONIC CONTROL UNIT

LOVATO ELECTRIC
RGK420 SA



Functions: manual start, remote start, periodic test

Multimeter V (L1, L2, L3, N), A (L1), Hz, kVA, battery V, hour counter

Backlit LCD display. Optical port and NFC

COMAP
IntelliLite 9



Functions: automatic or manual start, remote start, periodic test

Multimeter V (L1, L2, L3, N), A (L1, L2, L3), Hz, kVA, battery V, hour counter

Backlit LCD display. USB port

Communication accessories available: Ethernet, GSM-GPRS, 4G, GPS

OPTIONAL ELECTRONIC CONTROL UNIT




DEEP SEA DSE4520 MKII
DEEP SEA DSE7320 MKII





COMAP AMF25

SOUNDPROOF AND WEATHERPROOF CANOPY



<i>Self-supporting frame material</i>	<i>Carbon steel sheet, electro-welded, minimum thickness 2,5 mm</i>
<i>Soundproof canopy material</i>	<i>Carbon steel sheet, electro-welded, thickness between 1,5 and 4,5 mm</i>
<i>Painting</i>	<i>Epoxy powder RAL 5015 textured, outdoor-proof</i>
<i>In-built fuel tank</i>	100 lt + Drip tray
<i>Soundproofing coating material</i>	<i>Polyurethane finished with water-repellent and anti-oil fabric. Fire resistance EN13501-1 class B</i>
<i>Muffler</i>	<i>In-built the canopy. Residential type with sound reduction 35 dB(A)</i>
<i>Access openings</i>	<i>n.2 doors with key lock</i>
<i>Electric panel</i>	<i>Short side position. Dedicated protective door with padlockable lock and porthole (only GS with automatic panel)</i>
<i>Fresh air intake and hot air expulsion</i>	
<i>Lifting system</i>	<i>n.4 lifting hooks</i>
<i>Support feet</i>	<i>n.4 support feet with holes for machine ground fastening</i>

CONTAINER TRANSPORTABILITY ADVANTAGES

VERSION	20' BOX	40' BOX	40' HC
 <i>N. transportable pieces</i>	6	13	13
	6	13	26

MAIN OPTIONS



45A automatic transfer switch (ATS)



200 Lt bigger fuel tank with drip tray



750W engine preheating system



Automatic fuel transfer kit with manual by-pass system



Residual current circuit breaker



Electric fuel floater to check the fuel level from the electronic control unit



Engine oil pressure and cooling water temperature measuring instruments

OTHER OPTIONS

Power distribution socket set

Synchronizing electric panel

Battery switch

Remote control systems

ETHERNET, 2G - 3G - 4G, GPS

Further alternator brand

Quick couplings for connecting an external tank with three way valve

Outdoor, underground and transportable tanks

Slow or fast towing trailer

Front hot air expulsion canopy

Further colors

VERSIONS WITH SPECIAL EQUIPMENT



RENTAL

Special version with features designed for the rental market



ZERO NOISE

Super sound-proofed special version, noise level 50, 55 or 60 dB(A)

Greenpower AB
Helsingborgsvägen Varalöv,
262 96 Ängelholm, Sweden
Phone: +46 43122240
Email: info@greenpower.se
Web: www.greenpower.se