

# AS2

## MODULAR SYSTEM LABELING SERIES "AS2"

### MAIN FEATURES

- Structure and carpentry stainless steel and aluminum.
- Transport from 2 belts closed loop. Possible configurations:

Input belt size	Output belt size
240x750	240x400
240x750	240x750
240x1000	240x1000
240x1200	240x1000
330x510	330x750
330x750	330x750
330x1000	330x1000

- Power supply: voltage 230 Vac +/- 5%; 50-60 Hz.
- Operating temperature - 10 °C + 40 °C.
- Capacity transportable from 1 g to 10 kg.
- Machine managed by PLC.
- Brushless motors and drive boards.
- Protection IP40 transport and motors, IP65 front electrical panel.
- Moving dx/sx linear axis and bearings for positioning the print head and applies or applicator (**optional**).



### OPTIONS ON REQUEST

- Flash SAP.S.
- Flash AP.S.



STAINLESS  
STEEL



#### Postadress:

TRÄDGÅRDSTEKNIK AB  
Helsingborgsvägen 578, Varalöv  
262 96 ÄNGELHOLM

Telefon : 0431-222 90  
Bg.nr : 5743-7980  
Org.nr : 556409-6120

#### URL:

[www.tradgardsteknik.se](http://www.tradgardsteknik.se)  
E-postadress:  
[info@tradgardsteknik.se](mailto:info@tradgardsteknik.se)