



AUTOMATIC PRINT AND APPLY LABELLING TO AIR BLAST SERIES "SAP.A"

MAIN FEATURES

- Carter applicator made entirely of stainless steel.
- Label application by compressed air (AIR BLAST), complete with pressure regulator with air filter and pressure gauge, pressure regulator shot with pressure gauge.
- RS.M.ETIK chamber firing multi-labels with mechanical adjustment and position indicator size to 110x150 mm.
- Print width: 2", 3", 4".
- Print speed: 300 mm/s.
- Print mode: direct thermal (optional thermal transfer).
- Resolution: 200 dpi (300 dpi optional).
- Predisposition for fixing to the arm movement.
- Photocell detection product for the activation of the cycle pose.
- Communication ports: RS232 serial port, USB.
- Roll size, outer diameter: 220 mm max, internal diameter: 45 mm.
- Power supply voltage: 220/240 Vac; 50-60 Hz, on request: 110 Vac.


OPTIONS ON REQUEST

- Positioner column entirely in stainless steel, horizontal and vertical movement on bearings.
- Pedestal for positioning the column entirely stainless steel complete with stainless steel leveling feet.

INTERFACE ON REQUEST

Ethernet/Wi-Fi.













Postadress:

TRÄDGÅRDSTEKNIK AB Helsingborgsvägen 578, Varalöv 262 96 ÄNGELHOLM URL:

Telefon: 0431-222 90

Org.nr: 556409-6120

Bq.nr: 5743-7980

www.tradgardsteknik.se

E-postadress:

info@tradgardsteknik.se