

# Bottle filler with silver powder-coated finish & pedestal, freeze-resistant

## FEATURES & BENEFITS

### PUSH BUTTON

Polished chrome-plated push-button requires less than 5 lbs. (2.7 kg) of push force to activate.

### FREEZE-RESISTANT VALVE

Fully engineered system with the pneumatic-operated, freeze-resistant valve mounted in a cabinet that is installed on the inside wall where room temperature does not drop below 50° F (10° C). When valve goes to off position, water left in supply line between valve and bubbler drains back into waste inside cabinet, protecting the unit from freezing, and allowing fountain to function year-round.

### BARRIER-FREE

Barrier-free capabilities combined with its ease of use allows for a number of installation location possibilities.

## OPTIONS

- ❑ Drinking Fountain, Freeze Resistant ODBF: Model 3680FR, freeze-resistant drinking fountain for the 3600 series modular outdoor pedestals. Available in three standard colors - order 3680FR-01 silver, 3680FR-02 blue, and 3680FR-03 green.
- ❑ Mounting System: Model MTG.3501, galvanized steel anchors.
- ❑ Dog Bowl, Freeze Resistant ODBF: Model 3670FR, freeze-resistant dog bowl for the 3600 series modular outdoor pedestals. Available in three standard colors - order 3670FR-01 silver, 3670FR-02 blue, and 3670FR-03 green.
- ❑ Pedestal Arm, ODBF: The 3671 pedestal arm allows for the mounting of the 3690 series bottle fillers or the 3680 series drinking fountains. Includes the model 3655 bottom access plate. Available in three standard colors - order 3671-01 silver, 3671-02 blue, and 3671-03 green.

## SPECIFICATIONS

Model 3620FR modular outdoor, barrier-free, freeze-resistant pedestal bottle filler shall include a 3/16" steel pedestal with phosphating and silver powder-coating, two bottle filling stations, fully engineered pneumatic valve assembly, large-opening bottle filler with quick-fill 1 gpm flow rate, 100% lead-free waterways, polished chrome-plated vandal-resistant waste strainers, vandal-resistant access plates, integral mounting feet, and 1-1/2" slip waste. REQUIRES MODEL 6518.2FR PRICED SEPARATELY.

## APPLICATIONS

The 3620FR offers a solution for the changing needs of outdoor settings as well as outdoor wheelchair access, appealing to all users through accessibility and safety. This outdoor bottle filler is ideal in areas such as parks, schools, and other outdoor areas where hydration facilities are needed. Model meets all current Federal Regulations for the disabled including those in the Americans with Disabilities Act, and complies with Prop 65. Certified by CSA to NSF/ANSI 61, section 9 and NSF/ANSI 372; and was evaluated to be compliant to US and Canada Plumbing Codes including Uniform Plumbing Code (UPC), International Plumbing Code (IPC) and National Plumbing Code of Canada (NPC).

### Postadress:

TRÄDGÅRDSTEKNIK AB  
Helsingborgsvägen 578, Varalöv  
262 96 ÄNGELHOLM

Telefon : 0431-222 90  
Bg.nr : 5743-7980  
Org.nr : 556409-6120

### URL:

[www.tradgardsteknik.se](http://www.tradgardsteknik.se)  
E-postadress:  
[info@tradgardsteknik.se](mailto:info@tradgardsteknik.se)

