

MINI CHECK

CHECKWEIGHER SERIES "MINI CHECK"

MAIN FEATURES

- Rates up to 35 ppm.
- Capacity: 6 kg-2 g/15 kg-5 g/30 kg-10 g.
- Motorized weighing belt closed loop 355x570.
- Expulsion with belt engines and two-way.
- Backlit graphic display Touch Screen, l x h size = 120x90 mm.
- Light column Led out of tolerance (optional).
- Machine managed by PLC.
- Brushless motors and drive boards, speed 40 m/min.
- Protection IP68 Touch Screen, IP40 transport and motors, IP65 front electrical panel.
- Operating temperature - 10 °C + 40 °C.
- Structure and carpentry of aluminum and stainless steel.
- Power supply: voltage 230 Vac +/-5%, Hz 50/60.
- Consumption 0.75 kW.



SELECTABLE FUNCTIONS

- Programmable function keys to customize the keyboard functions according to needs.
- Tolerance check:
 - to target, through article database, with setting of 3 tolerance thresholds, for the physical division of the packs into 7 different groups.
 - programmable weight thresholds (min/max), with archive.
 - in weight thresholds (min/max), with quick entry.
- Calculation and printing of statistics and of the standard deviation of the executed weighs.
- Static or dynamic automatic zero function of the belt (max. 2% of the capacity) after a programmable number of weighs.
- Advanced management of barcodes, with the possibility of storing, processing and printing 5 different codes.
- Automatic printing/reset of the partial total after a programmable number of weighs.
- Printing at each executed weigh and eventual automatic storage in the alibi memory.
- Completely programmable printouts, for compatibility with any ASCII printer manageable through the serial port.
- Database 1000 articles each with:
 - alphanumeric description, target and thresholds of tolerance.
- Setting the stocking density, for each article, for weighing in ml.
- Pretara and delay activation of the ejector programmable for each article.
- Programming manual article or with software on your PC.
- Article selection through barcode reading.



I/O SECTION

- 1 RS232 serial port.
- 1 RS232/RS485 serial port.
- External Profibus interface (optional).
- Labeling for totalization (optional).

INTERFACE ON REQUEST

- USB/Ethernet/Wi-Fi/Bluetooth.



Postadress:

TRÄDGÅRDSTEKNIK AB
Helsingborgsvägen 578, Varalöv
262 96 ÄNGELHOLM

Telefon : 0431-222 90
Bg.nr : 5743-7980
Org.nr : 556409-6120

URL:

www.tradgardsteknik.se
E-postadress:
info@tradgardsteknik.se